

Safety Data Sheet (SDS)

Date of Issue: December 1, 2007

Date Revised: 1st April, 2021

1. Identification of the Substance and of the Company

Product Identifier:

Tool Holder and the components

Supplier Information:

Company Name: NGK SPARK PLUG CO., LTD.
 Contact Department: Machining Technology Company
 Address: 2808 Iwasaki, Komaki-shi, Aichi, Japan <485-8510>
 Telephone Number: +81-568-76-1270
 FAX Number: +81-568-76-1288
 Emergency Telephone : +81-568-76-1270

Recommended Use and Restrictions on Use of the Tool Holder

Tool Holder mainly for holding cutting tool, etc.

Attention to the Phase/State of the Tool Holder

- Tool Holder as solid state is chemically stable and safe at explosive, flammable, combustible, pyrophoric, water-reactive, and oxidizability under normal environment.
- Tool Holder is safe for use as the cutting tools under normal condition.
- This SDS informs about the dust, fume or vapor which occur from Tool Holder producing process such as raw material powder handling and grinding.

2. Hazard Identification

The GHS Classification

Some data (such as the burning rate test data, etc.) for the dust, fume or vapor which occur from Tool Holder producing process are unavailable. Therefore, they are not be classified by GHS.

In here, GHS classification of the each metallic ingredients (cobalt, nickel, chromium and manganese) for composing the Tool Holder can be disclosed. In addition, other hazards and harmful effects (for health, environment, physical and chemical) which are not listed are unclassifiable or non-applicable by GHS.

GHS classification for the hazards of cobalt alone in below,
 (When cobalt is included as ingredients of Tool Holder.)

Health Hazard	<ul style="list-style-type: none"> • Respiratory sensitization • Skin sensitization • Carcinogenicity • Reproductive toxicity • Specific target organ toxicity (Single exposure) • Specific target organ toxicity (Repeated exposure) 	Category1 Category1 Category2 Category2 Category3 (Respiratory tract irritation) Category1 (Respiratory)
Environmental Hazard:	• Hazardous to the aquatic environment	Category4

GHS classification for the hazards of nickel alone in below,
 (When nickel is included as ingredients of Tool Holder.)

Health Hazard	<ul style="list-style-type: none"> • Respiratory sensitization • Skin sensitization 	Category1 Category1
---------------	---	------------------------

	<ul style="list-style-type: none"> • Carcinogenicity • Specific target organ toxicity (Single exposure) • Specific target organ toxicity (Repeated exposure) 	Category2 Category1 (Respiratory tract irritation) Category1 (Respiratory)
Environmental Hazard:	• Hazardous to the aquatic environment	Category4

GHS classification for the hazards of chromium alone in below,
 (When chromium is included as ingredients of Tool Holder.)

Health Hazard	<ul style="list-style-type: none"> • Serious eye damage • Respiratory sensitization • Skin sensitization • Germ cell mutagenicity • Specific target organ toxicity (Single exposure) • Specific target organ toxicity (Repeated exposure) 	Category2B Category1 Category1 Category2 Category2 (Respiratory tract irritation) Category3 (Respiratory)
---------------	---	--

GHS classification for the hazards of manganese alone in below,
 (When manganese is included as ingredients of Tool Holder.)

Health Hazard	<ul style="list-style-type: none"> • Skin corrosion, irritation • Serious eye damage • Reproductive toxicity • Specific target organ toxicity (Single exposure) • Specific target organ toxicity (Repeated exposure) 	Category3 Category2B Category1B Category1 (Respiratory) Category1 (Nervous system , Respiratory)
Environmental Hazard:	• Hazardous to the aquatic environment	Category4

GHS Label Elements

GHS label elements of the each metallic ingredients (cobalt, Nickel, chromium and manganese) for composing the Tool Holder can be disclosed in below.

	Cobalt	Nickel	Chromium	Manganese
Hazard Pictograms :				
Signal Words :	Danger			
Hazard Statements :	<ul style="list-style-type: none"> • Risk of causing allergies, asthma or breathing difficulties if inhaled. • Risk of causing an allergic skin reaction. • May cause 	<ul style="list-style-type: none"> • Risk of causing allergies, asthma or breathing difficulties if inhaled. • Risk of causing an allergic skin reaction. • May cause 	<ul style="list-style-type: none"> • Risk of causing allergies, asthma or breathing difficulties if inhaled. • Risk of causing an allergic skin reaction. • Suspected of 	Mild skin irritation <ul style="list-style-type: none"> • Eye irritation. • Respiratory disorders. • May cause adverse effects on fertility or the unborn child.

	<p>cancer.</p> <ul style="list-style-type: none"> • May cause adverse effects on fertility or the unborn child. • Risk of respiratory irritation. • Cause of respiratory failure due to long-term or repetitive exposure. • May be harmful to aquatic life due to long-term effects 	<p>cancer.</p> <ul style="list-style-type: none"> • Respiratory and kidney disorders • Cause of respiratory failure due to long-term or repetitive exposure. • May be harmful to aquatic life due to long-term effects 	<p>causing genetic disease</p> <ul style="list-style-type: none"> • Failure to systemic toxicity • Risk of respiratory irritation. 	<ul style="list-style-type: none"> • Nervous system and respiratory disorders due to long-term or repetitive exposure. • May be harmful to aquatic life due to long-term effects
<p>Precautionary Statements :</p>	<p>【Prevention】</p> <ul style="list-style-type: none"> • Obtain safety instructions* before use. • Do not handle until all safety precautions have been read and understood. • Use appropriate personal protection and ventilation system keeping away from exposure. • Wear suitable protective gloves. • When insufficient ventilation, wear respirator as required. • Do not breathe dust, fume or vapor. • Do not eat, drink or smoke in handling area. • Wash skin thoroughly after handling. • Do not release into the environment. <p>【Responses】</p> <ul style="list-style-type: none"> • If inhaled, move to fresh air and take a rest with posture easy to breathe. • If respiratory symptoms occurs, contact a doctor. • When feeling ill, get medical advice/attention. • Take off contaminated clothing and wash before reuse. • If on skin, rinse away immediately with a large amount of water and soap. • If skin irritation occurs, contact a doctor and get medical advice/attention. • If exposed or concerned, get medical advice/attention. • If dust is in eyes, immediately wash away with clean water (remove the contact lenses if possible). If irritation persists, get medical advice/attention. • If a large amount of dust is swallowed, get medical advice/attention after ingesting plenty of water to dilute. <p>【Storage】</p> <ul style="list-style-type: none"> • Avoid sudden changes of temperature and high humidity for storage. <p>【Disposal】</p> <ul style="list-style-type: none"> • Dispose of contents/container to an approved waste disposal plant under the laws. 			

*For safety instructions, refer to the Japan Cutting & Wear-resistant Tool Association website (<http://www.jta-tool.jp/>) .

3. Composition/Information on Ingredients

- Distinction between substance and mixture: Mixture (alloy)
- Tool Holder may be coated or surface treated with the following substances.

Coating materials : Ni,Cr

Surface treatment : Steam treatment (Fe_3O_4), Nitriding treatment (Fe_4N , Fe_2N)

Ingredients and concentration or concentration range (composition) of the Tool Holder

Ingredient	Chemical Formula	CAS No	Official Number of Law for PRTR	Official Number of Industrial Safety and Health Law	Composition mass%
Manganese	Mn	7439-96-5	Class1:412	Appendix 9-550	0-3
Silicon	Si	7440-21-3	N/A	N/A	0-5
Nickel	Ni	7440-02-0	Class1:308	Appendix 9-418	0-18
Chromium	Cr	7440-47-3	Class1:87	Appendix 9-142	0-13
Vanadium	V	7440-62-2	N/A	N/A	0-18
Tungsten	W	7440-33-7	N/A	Appendix 9-337	0-11
Molybdenum	Mo	7439-98-7	Class1:453	Appendix 9-603	0-10
Cobalt	Co	7440-48-4	Class1:132	Appendix 9-172	0-11
Copper	Cu	744050-8	N/A	N/A	0-2
Iron	Fe	7439-89-6	N/A	N/A	RM

*Even if the cemented carbide do not contain cobalt, nickel, chromium, manganese as an active ingredient may include cobalt, nickel, chromium, manganese as an impurity.

4. First-Aid Measures

If Inhaled

- If the high concentration of dust is inhaled or respiratory symptoms (coughs, gasping, shortness of breath, etc.) are experienced, move to fresh air and take a rest with posture easy to breathe. If breathing difficulties occur, administer oxygen inhalation. If breathing has stopped, immediately administer artificial respiration and get medical advice/attention.
- If irritation or rash persists, get medical advice and attention.

If on Skin

- If dust is contacted with skin, take off contaminated clothing and rinse the affected area with soapy water thoroughly. If irritation or rash persists, get medical advice/attention.

If in Eyes

- If dust is in eyes, immediately wash away with clean water (remove the contact lenses if possible). If irritation persists, get medical advice/attention.

If Swallowed

- If a large amount of dust is swallowed, get medical advice/attention after ingesting plenty of water to dilute.

5. Fire-Fighting Measures

Extinguishing Media

- To extinguish the fire of dust, use dry sand, expanded vermiculite, dilatable perlite, ABC type (general, oil, electric fire) powder extinguishers or water (no water allowed for the dust containing cut powders of light metal such as magnesium and aluminum).

Special Protective Actions for Fire-Fighters

- In fighting a fire, wear a protective clothing, dust-proof respirator or respiratory protective equipment.

6. Accidental Release Measures

Personal Precautions

- It is recommended that someone who cleans dust should wear clothing and respiratory protective equipment to minimize exposure.

Environmental Precautions

- Dispose of dust as industrial wastes and prevent release in water systems.

Containment and Cleanup Methods and Equipment

- If there is dust which occur from Tool Holder producing process, isolate the area and remove with a cleaner equipped with a filter which can take up fine particles very efficiently. If appropriate removing methods are not available, sweep with water sprayers or wet mops.

7. Handling and Storage

Handling

- If the disperse of dust containing cobalt or nickel or manganese is concerned, provide local exhaust ventilation and use personal protective equipment to minimize exposure to human body.
- Obtain safety instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Do not breathe dust, fume or vapor.
- Do not eat, drink or smoke in handling area.
- Wash skin thoroughly after handling.
- Do not release into the environment.

Storage

- Avoid sudden changes of temperature and high humidity for storage.

8. Exposure Controls/Personal Protection

Exposure Prevention

- Permissible concentration in working environment (reference value)

Ingredient	Chemical Formula	OSHA* PEL* mg/m ³	ACGIH* TLV* mg/m ³	Japan Society for Occupational Health Exposure Limit mg/m ³
Manganese	Mn	5.0	0.2	0.3
Silicon	Si	15	10	N/A
Nickel	Ni	1.0	1.5	1.0
Chromium	Cr	0.5	0.5	0.5
Vanadium	V	N/A	N/A	N/A
Tungsten	W	5	5.0	N/A
Molybdenum	Mo	15	10	N/A
Cobalt	Co	0.1	0.02	0.05
Copper	Cu	1.0	1.0	N/A
Iron	Fe	N/A	N/A	N/A

*OSHA : Occupational Safety & Health Administration U.S. Department

*PEL : Permissible Exposure Limit

*ACGIH : American Conference of Governmental Industrial Hygienists Inc.

*TLV : Threshold Limit Value

*N/A : Not Applicable

- Facility measures

Provide local exhaust ventilation so that dusts in the air may not exceed the exposure

limits in the above table. It is to be noted that management concentration of the cobalt (and its inorganic compounds) and manganese (and its inorganic compounds) are to be 0.02mg/m³ and 0.2mg/m³ respectively in accordance with the working environment assessment standard by Japanese Minister of Health, Labour and Welfare under the paragraph (2), Article 65-2 of the Industrial Safety and Health Act in Japan.

In addition, cobalt (and its inorganic compounds) and manganese (and its inorganic compounds) in the storage or handling, and that to take the necessary action conforming to the Ordinance on Prevention of Hazards due to Specified Chemical Substance.

Protection Measures

- Respiratory Protection: Dust-proof respirators and respiratory protective equipment are recommended.
- Hand Protection: Protective gloves for dust are recommended.
- Eye Protection: Protective glasses for dust are recommended.
- Skin/Body Protection: Avoid direct skin contact.
Clean up deposited dust on clothing, rags, etc. by washing or absorbing with suitable filters but not by whisking off.
Change the contaminated clothing into clean one.

Hygiene Measure

Wash skin thoroughly after handling.

9. Physical and Chemical Properties

Appearance:	Shiny silver(Surface grinding state) , Dark gray, etc. (in case of the coated or surface treated Tool Holder, the appearance color is often different.)
Odor:	Odorless
pH:	No data available
Melting Point:	1200 – 1400 °C
Boiling Point:	No data available
Flash Point:	No data available
Vapor Pressure:	No data available
Specific Gravity:	7 – 9
Solubility:	Insoluble

10. Stability and Reactivity

A grain of dust which occur from Tool Holder producing process is very fine and under the specific conditions in which the dusts are mixed with grinding oil with low flash point, it is possible to become pyrophoric. If dusts under very flammable conditions are dispersed in the air, it is possible to explode.

The each metallic ingredients (cobalt, Nickel, chromium and manganese) for composing the Tool Holder has the following information about stability and reactivity under specific conditions.

Stability and reactivity of cobalt alone in below,
(When cobalt is included as ingredients of Tool Holder.)

Stability:	Stable to heat and contact with water Ignite spontaneously in air
Hazardous reactions:	It reacts with strong oxidizing agents It reacts violently with oxygen, and it poses a risk of fire or explosion It reacts violently with acid to generate hydrogen
Conditions to avoid:	Contact with incompatible materials
Incompatible materials:	Strong oxidizing agents, acid

Hazardous decomposition products: By combustion, cobalt oxide and fumes of cobalt oxide may occur

Stability and reactivity of nickel alone in below,
(When nickel is included as ingredients of Tool Holder.)

Stability: It is considered stable in storage and handling in accordance with the laws and regulations

Hazardous reactions: Metallic nickel is usually stabilized against oxidation by the oxide film, fresh metal surfaces without oxide film is rapidly oxidized by air. Thus, fresh metallic nickel powder, there is a risk of ignition in air.

Conditions to avoid: No data available

Hazardous decomposition products: No data available

Stability and reactivity of chromium alone in below,
(When chromium is included as ingredients of Tool Holder.)

Stability: Stable under normal handling conditions

Hazardous reactions: Reacts violently with strong oxidizing agents such as hydrogen peroxide, it poses a risk of fire or explosion.

It reacts with dilute hydrochloric acid and dilute sulfuric acid.

Conditions to avoid: The alkali or alkaline carbonate is Incompatible.
When mixed with air in powder or granular form, there is a possibility of dust explosion.

Incompatible materials: Strong oxidizing agents, dilute hydrochloric acid, dilute sulfuric acid, alkali, alkali carbonate

Hazardous decomposition products: During combustion, there can be irritating or toxic fumes and gases.

Stability and reactivity of manganese alone in below,
(When manganese is included as ingredients of Tool Holder.)

Stability: Stable under normal handling conditions.

Hazardous reactions: Toxic fumes occur when heated.

Reacts violently with nonmetals (chlorine, fluorine, oxygen, etc.) at high temperature, causing fire and explosion hazard.

Reacts violently with hydrogen peroxide, bromine pentafluoride, nitrogen dioxide and aluminum dust, causing fire and explosion hazard.

It reacts with boron, carbon, silicon, phosphorus, sulfur, oxidant.

It reacts explosively with nitric acid and ammonium nitrate.

In the case of powder, it reacts with water or steam to generate hydrogen.

When mixed with air in powder or granular form, there is a possibility of dust explosion.

Conditions to avoid: High temperature heating, mixing and contact with incompatible hazardous substances.

Strong oxidants, strong acids, hydrogen peroxide, bromine pentafluoride, nitrogen dioxide, nonmetals, aluminum dust, etc.

Hazardous decomposition products: Upon heating, irritating, corrosive, toxic gases and fumes are generated.

11. Toxicological Information

Acute Toxicity:	No data available on Tool Holder
Skin Corrosion/Irritation:	No data available on Tool Holder
Serious Eye Damage/Eye Irritation:	No data available on Tool Holder
Respiratory or Skin Sensitization:	No data available on Tool Holder
Germ Cell Mutagenicity:	No data available on Tool Holder
Carcinogenicity:	Group 2A on IARC, as cobalt powder coexisting with tungsten carbide powder. Suspected to be carcinogenic in humans (Ref.1)
Reproductive Toxicity:	No data available on Tool Holder
Specific Target Organ Toxicity/Systemic Toxicity: (Single Exposure)	No data available on Tool Holder
Specific Target Organ Toxicity/Systemic Toxicity: (Repeated Exposure)	No data available on Tool Holder
Aspiration Hazard:	No data available on Tool Holder

12. Ecological Information

- The aquatic environment acute hazard**
- Not reported on Tool Holder
- The aquatic environment chronic hazard**
- Not reported on Tool Holder
- Mobility**
- Not reported on Tool Holder

13. Disposal Considerations

- Safe and environmentally desirable disposal method**
- The ingredients such as tungsten carbide, cobalt, nickel are rare metal. It is desirable to collect and recycle them.
 - For disposal, conform to the applicable laws regarding industrial wastes such as 'Waste Disposal and Public Cleansing Law' and relevant local by laws.

14. Transport Information

International Regulations

UN Number:	Not applicable
UN Hazard Class:	Not applicable
Marine Pollutant:	Not applicable

Domestic Regulations

Land Regulatory Information	Not applicable
UN Number:	Not applicable
UN Hazard Class:	Not applicable
Marine Pollutant:	Not applicable

15. Regulatory Information

- Law for Pollutant Release and Transfer Register (PRTR)
 - Cobalt: "Class 1 designated chemical substances", Cabinet Order No.132
 - Nickel: "Class 1 designated chemical substances", Cabinet OrderNo.308
 - Chromium: "Class 1 designated chemical substances", Cabinet OrderNo.87
 - Molybdenum: "Class 1 designated chemical substances", Cabinet Order No.453
 - Manganese: "Class 1 designated chemical substances", Cabinet OrderNo.412

- Industrial Safety and Health Law, Ordinance on Prevention of Hazards due to Specified Chemical Substances

Cobalt: The substances are defined in the Article 57-2 of the Act, and the cobalt is listed by No.172 in Appended Table9 in the Article 18-2 of the Enforcement Order as “Dangerous or Harmful Substances to be notified their names, etc.”

Article 2, Paragraph 1, Items 2 and 5 of Ordinance on Prevention of Hazards due to Specified Chemical Substance, Specified chemical substance class 2, Management class 2.

When the content of cobalt and cobalt oxide is less than 1%, the Ordinance on Prevention of Hazards due to Specified Chemical Substance is not covered.

Nickel: The substances are defined in the Article 57-2 of the Act, and the nickel is listed by No.418 in Appended Table9 in the Article 18-2 of the Enforcement Order as “Dangerous or Harmful Substances to be notified their names, etc.”

Chromium: The substances are defined in the Article 57-2 of the Act, and the chromium is listed by No.142 in Appended Table9 in the Article 18-2 of the Enforcement Order as “Dangerous or Harmful Substances to be notified their names, etc.”

Molybdenum: The substances are defined in the Article 57-2 of the Act, and the molybdenum is listed by No.603 in Appended Table9 in the Article 18-2 of the Enforcement Order as “Dangerous or Harmful Substances to be notified their names, etc.”

Manganese: The substances are defined in the Article 57-2 of the Act, and the manganese is listed by No.550 in Appended Table9 in the Article 18-2 of the Enforcement Order as “Dangerous or Harmful Substances to be notified their names, etc.”

Article 2, Paragraph 1, Items 2 and 5 of Ordinance on Prevention of Hazards due to Specified Chemical Substance, Specified chemical substance class 2, Management class 2.

When the content of cobalt and cobalt oxide is less than 1%, the ordinance on Prevention of Hazards due to Specified Chemical Substance is not covered.

Tungsten: The substances are defined in the Article 57-2 of the Act, and the tungsten is listed by No.337 in Appended Table9 in the Article 18-2 of the Enforcement Order as “Dangerous or Harmful Substances to be notified their names, etc.”

16. Other Information

Other Hazardous Information

The following attention should be paid for dust which occur from Tool Holder producing process.

- If a large amount of dust containing cobalt is inhaled, blood, heart, thyroid gland, and spleen disorders may result. (Ref.2)
- It is reported that repeated or prolonged contact with cobalt, nickel or chromium may affect skin, respiratory organs, heart, etc. (Ref.3 - 6)
- Contact with molybdenum stimulates skin and eyes. Also, inhalation and swallowing of molybdenum may be harmful. (Ref.7)
- For carcinogenicity of metallic ingredients of Tool Holder has the following knowledge.

Cobalt metal	ACGIH	A3: Confirmed animal carcinogen with unknown relevance to humans.
--------------	-------	---

	IARC	2B: Possibly carcinogenic to humans.
	Japan Society for Occupational Health	2B: The substance has been determined to be possibly carcinogenic to humans (with relatively insufficient evidence).
Nickel metal	ACGIH	A5: Not suspected as a human carcinogen.
	IARC	2B: Possibly carcinogenic to humans.
	Japan Society for Occupational Health	2B: The substance has been determined to be possibly carcinogenic to humans (with relatively insufficient evidence).
Chromium metal	IARC	3: Not classifiable as to its carcinogenicity to humans.

*ACGIH : American Conference of Governmental Industrial Hygienists Inc.

*IARC : International Agency for Research on Cancer

Disclaimer

The contents of this SDS are based on material and information available as of today and may be revised due to knowledge newly obtained. The values of concentration, physical/chemical properties are not guaranteed. In addition, the precautions described herein apply only to normal uses, and thus safety cannot be guaranteed.

Reference URL

- Ministry of Economy, Trade and Industry : <http://www.meti.go.jp/>
- Ministry of the Environment : <http://www.env.go.jp/>
- Ministry of Health, Labour and Welfare : <http://www.mhlw.go.jp/>
- Japan Industrial Safety and Health Assoc. : <http://www.jaish.gr.jp/>
- International Agency for Research on Cancer : <http://monographs.iarc.fr/>
- International Chemical Safety Card : <http://www.nihs.go.jp/ICSC/>
- National Institute of Technology and Evaluation : <http://www.safe.nite.go.jp/ghs/list.html>

Reference Documents

- (1) IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, vol.86 (2006).
- (2) Food & Drug Research Laboratories, study No.8005B (4.11.84).
- (3) T. Shirakawa et al., Chest. 95, 29 (1989).
- (4) International Chemical Safety Cards (cobalt, chromium, nickel).
- (5) The Guide to Chemical Hazards (edited by Japan Industrial Safety & Health Association)
- (6) A. O. Bech et al., Brit. J. Ind., 19, 239 (1962).
- (7) Chemical safety management data book, (The Chemical Daily Co., Ltd.)

Revision History

	Date	Contents
Rev.4	1 st April, 2021	GHS classification revised. The change of Contact Department Name.