

Safety Data Sheet (SDS)

Date of Issue: 27th April, 2012

Date Revised: 3rd April, 2023

1. Identification of the Substance and of the Company

Product Identifier:

PCD (Polycrystalline diamond) and Cemented Carbide base metal
(hereinafter referred to “PCD/Cemented Carbide”)

Supplier Information:

Company Name: NTK CUTTING TOOLS .CO., LTD.
 Address: 2808 Iwasaki, Komaki-shi, Aichi, Japan <485-8510>
 Telephone Number: +81-568-76-1270
 FAX Number: +81-568-76-1288
 Emergency Telephone : +81-568-76-1270

Recommended Use of the PCD/Cemented Carbide

Cutting and drilling tools for metallic material

Restrictions on Use of the PCD/Cemented Carbide

Do not use for other than the specified purpose

Attention to the Phase/State of the PCD/Cemented Carbide

- PCD/Cemented Carbide as solid state is chemically stable and safe at explosive, flammable, combustible, pyrophoric, water-reactive, and oxidizability under normal environment.
- PCD/Cemented Carbide are safe for use as the cutting tools (grinding, machining, rolling for metals) under normal condition.
- This SDS informs about the dust, fume or vapor which occur from PCD/Cemented Carbide producing process such as raw material powder handling and grinding.

2. Hazard Identification

The GHS Classification

Some data (such as the burning rate test data, etc.) for the dust, fume or vapor which occur from PCD/Cemented Carbide producing process are unavailable. Therefore, they are not be classified by GHS.

In here, GHS classification of the each metallic ingredients (cobalt) for composing the PCD/Cemented Carbide can be disclosed. In addition, other hazards and harmful effects (for health, environment, physical and chemical) which are not listed are unclassifiable or non-applicable by GHS.


GHS classification for the hazards of cobalt alone in below,
(When cobalt is included as ingredients of PCD/Cemented Carbide.)

Health Hazard	<ul style="list-style-type: none"> • Acute toxicity (oral) • Acute toxicity (inhaled: dust, mist) • Serious eye damage / eye irritation • Respiratory sensitization • Skin sensitization • Carcinogenicity • Reproductive toxicity • Specific target organ toxicity (Single exposure) • Specific target organ toxicity (Repeated exposure) 	<ul style="list-style-type: none"> Category4 Category1 Category2B Category1A Category1A Category2 Category1B Category1 (Respiratory) Category1 (Respiratory, Heart, Thyroid, Blood)
---------------	---	--

Environmental Hazard:	<ul style="list-style-type: none"> • Hazardous to the aquatic environment - prolonged (Chronic hazard) • Hazardous to the aquatic environment - repeated (Acute hazard) 	<p>Category1</p> <p>Category1</p>
-----------------------	---	-----------------------------------

GHS Label Elements

GHS label elements of the each metallic ingredients (cobalt and chromium) for composing the PCD /Cemented Carbide can be disclosed in below.

	Cobalt	Chromium
Hazard Pictograms :		
Signal Words :	Danger	
Hazard Statements :	<ul style="list-style-type: none"> • Risk of causing allergies, asthma or breathing difficulties if inhaled. • Risk of causing an allergic skin reaction. • May cause cancer. • May cause adverse effects on fertility or the unborn child. • Risk of respiratory irritation. • Cause of respiratory failure due to long-term or repetitive exposure. • May be harmful to aquatic life due to long lasting effects 	<ul style="list-style-type: none"> • Risk of causing allergies, asthma or breathing difficulties if inhaled. • Risk of causing an allergic skin reaction. • Suspected of causing genetic disease • Failure to systemic toxicity • Risk of respiratory irritation.
Precautionary Statements :	<p>【Prevention】</p> <ul style="list-style-type: none"> •Obtain safety instructions* before use. •Do not handle until all safety precautions have been read and understood. •Use appropriate personal protection and ventilation system keeping away from exposure. •Wear suitable protective gloves. •When insufficient ventilation, wear respirator as required. •Do not breathe dust, fume or vapor. •Do not eat, drink or smoke in handling area. •Wash skin thoroughly after handling. •Do not release into the environment. <p>【Responses】</p> <ul style="list-style-type: none"> • If inhaled, move to fresh air and take a rest with posture easy to breathe. •If respiratory symptoms occurs, contact a doctor. •When feeling ill, get medical advice/attention. •Take off contaminated clothing and wash before reuse. 	

<ul style="list-style-type: none"> • If on skin, rinse away immediately with a large amount of water and soap. • If skin irritation occurs, contact a doctor and get medical advice/attention. • If exposed or concerned, get medical advice/attention. • If dust is in eyes, immediately wash away with clean water (remove the contact lenses if possible). If irritation persists, get medical advice/attention. • If a large amount of dust is swallowed, get medical advice/attention after ingesting plenty of water to dilute. <p>【Storage】</p> <ul style="list-style-type: none"> • Avoid sudden changes of temperature and high humidity for storage. <p>【Disposal】</p> <ul style="list-style-type: none"> • Dispose of contents/container to an approved waste disposal plant under the laws.
--

*For safety instructions, refer to the Japan Cutting & Wear-resistant Tool Association website (<http://www.jta-tool.jp/>) .

3. Composition/Information on Ingredients

- Distinction between chemical substance and mixture: Mixture (alloy)
- Chemical name or general name: PCD/Cemented Carbide
- Ingredients and concentration or concentration range (composition) of the PCD/Cemented Carbide.

Ingredient	Chemical Formula	CAS No	Composition mass%
PCD layer			
Carbon	C	7440-44-0	30-95
Tungsten carbide	WC	12070-12-1	0-70
Cobalt	Co	7440-48-4	10-30
Cemented Carbide base metal			
Tungsten carbide	WC	12070-12-1	55-100
Tantalum carbide	TaC	12070-06-3	0-20
Niobium carbide	NbC	12069-94-2	0-20
Titanium carbide	TiC	12070-08-5	0-20
Titanium nitride	TiN	25583-20-4	0-5
Vanadium carbide	VC	12070-10-9	0-5
Cobalt	Co	7440-48-4	0-30
Chromium	Cr	7440-47-3	0-5

4. First-Aid Measures

If Inhaled

- If the high concentration of dust is inhaled or respiratory symptoms (coughs, gasping, shortness of breath, etc.) are experienced, move to fresh air and take a rest with posture easy to breathe. If breathing difficulties occur, administer oxygen inhalation. If breathing has stopped, immediately administer artificial respiration and get medical advice/attention.
- If irritation or rash persists, get medical advice and attention.

If on Skin

- If dust is contacted with skin, take off contaminated clothing and rinse the affected area with soapy water thoroughly. If irritation or rash persists, get medical advice/attention.

If in Eyes

- If dust is in eyes, immediately wash away with clean water (remove the contact lenses if possible). If irritation persists, get medical advice/attention.

If Swallowed

- If a large amount of dust is swallowed, get medical advice/attention after ingesting plenty of water to dilute

5. Fire-Fighting Measures**Suitable Extinguishing Media and Unsuitable Extinguishing Media**

- To extinguish the fire of dust, use dry sand, expanded vermiculite, dilatable perlite, ABC type (general, oil, electric fire) powder extinguishers or water (no water allowed for the dust containing cut powders of light metal such as magnesium and aluminum).

Special Protective Equipment and Emergency Procedures for Fire-Fighters

- In fighting a fire, wear a protective clothing, dust-proof respirator or respiratory protective equipment.

6. Accidental Release Measures**Personal Precautions, Protective Equipment, and Emergency Procedures**

- It is recommended that someone who cleans dust should wear clothing and respiratory protective equipment to minimize exposure.

Environmental Precautions

- Dispose of dust as industrial wastes and prevent release in water systems.

Containment and Cleanup Methods and Equipment

- If there is dust which occur from PCD/Cemented Carbide producing process, isolate the area and remove with a cleaner equipped with a filter which can take up fine particles very efficiently. If appropriate removing methods are not available, sweep with water sprayers or wet mops.

7. Handling and Storage**Handling****■ Technical Measures**

- If the disperse of dust containing cobalt is concerned, provide local exhaust ventilation and use personal protective equipment to minimize exposure to human body.

■ Precautions for Safe Handling

- Obtain safety instructions before use.
- Do not handle until all safety precautions have been read and understood.

■ Contact Avoidance

- Take measures described in "Exposure Controls/Personal Protection."
- Do not breathe dust, fume or vapor.
- Do not eat, drink or smoke in handling area.

■ Hygiene Measures

- Wash skin thoroughly after handling.
- Do not release into the environment.

Storage**■ Conditions for Safe Storage**

- Avoid sudden changes of temperature and high humidity for storage.
- If storing fine powder, dust, and swarf generated by cutting or polishing, cover them with a cover to prevent dispersal.

■ Materials for Safe Container

- Use materials meeting the specific gravity of PCD/Cemented Carbide.
-

8. Exposure Controls/Personal Protection

Exposure Prevention

• Permissible concentration in working environment (reference value)

Ingredient	Chemical Formula	OSHA* PEL* mg/m ³ (Metal Dust Concentration)	ACGIH* TLV* mg/m ³ (Metal Dust Concentration)	Japan Society for Occupational Health Exposure Limit mg/m ³
PCD layer				
Carbon	C	N/A	N/A	N/A
Tungsten carbide	WC	N/A	5 (as W)	N/A
Cobalt	Co	0.1	0.02	0.05
Cemented Carbide base metal				
Tungsten carbide	WC	N/A	5 (as W)	N/A
Tantalum carbide	TaC	N/A	N/A	N/A
Niobium carbide	NbC	N/A	N/A	N/A
Titanium carbide	TiC	N/A	N/A	N/A
Titanium nitride	TiN	N/A	N/A	N/A
Vanadium carbide	VC	N/A	N/A	N/A
Cobalt	Co	0.1	0.02	0.05
Nickel	Ni	1.0	1.5	1.0
Chromium	Cr	1.0	0.5	0.5

*OSHA : Occupational Safety & Health Administration U.S. Department

*PEL : Permissible Exposure Limit

*ACGIH : American Conference of Governmental Industrial Hygienists Inc.

*TLV : Threshold Limit Value

* Exposure Limit : If processing such as polishing and cutting that generates dust, for ingredients with not indicated value, refer to the exposure limit of the Japan Society for Occupational Health

*N/A : Not Applicable

• Facility measures

Provide local exhaust ventilation so that dusts in the air may not exceed the exposure limits in the above table. It is to be noted that management concentration of the cobalt (and its inorganic compounds) is to be 0.02mg/m³ in accordance with the working environment assessment standard by Japanese Minister of Health, Labour and Welfare under the paragraph (2), Article 65-2 of the Industrial Safety and Health Act in Japan.

In addition, cobalt (and its inorganic compounds) in the storage or handling, and that to take the necessary action conforming to the Ordinance on Prevention of Hazards due to Specified Chemical Substances.

Protection Measures

- Respiratory Protection: Dust-proof respirators and respiratory protective equipment are recommended.
- Hand Protection: Protective gloves for dust are recommended.
- Eye/Face Protection: Eye and face protections for dust are recommended.
- Skin/Body Protection: Avoid direct skin contact.
Clean up deposited dust on clothing, rags, etc. by washing or absorbing with suitable filters but not by whisking off.
Change the contaminated clothing into clean one.

Hygiene Measure

Wash skin thoroughly after handling.

9. Physical and Chemical Properties

Physical State:	Solid state
Color :	PCD: Black/Grey-metallic color Cemented Carbide: Dark grey color
pH:	No data available
Odor:	Odorless
Melting/Freezing Point:	No data available
Boiling or Initial Boiling Point and Boiling Range:	No data available
Flash Point:	No data available
Vapor Pressure:	No data available
Vapor density:	No data available
Kinematic Viscosity:	No data available
Solubility:	Insoluble
Density (Relative Density):	11.0-15.5

10. Stability and Reactivity

A grain of dust which occur from PCD/Cemented Carbide producing process is very fine and under the specific conditions in which the dusts are mixed with grinding oil with low flash point, it is possible to become pyrophoric. If dusts under very flammable conditions are dispersed in the air, it is possible to explode.

The each metallic ingredients (cobalt) for composing the PCD/Cemented Carbide has the following information about stability and reactivity under specific conditions.

Stability and reactivity of cobalt alone in below,

(When cobalt is included as ingredients of PCD/Cemented Carbide.)

Reactivity, chemical stability:	Stable to heat and contact with water Ignite spontaneously in air
Hazardous reactions:	It reacts with strong oxidizing agents It reacts violently with oxygen, and it poses a risk of fire or explosion It reacts violently with acid to generate hydrogen
Conditions to avoid:	Contact with incompatible materials
Incompatible materials:	Strong oxidizing agents, acid
Hazardous decomposition products:	By combustion, cobalt oxide and fumes of cobalt oxide may occur

11. Toxicological Information

Acute Toxicity:	No data available on PCD/Cemented Carbide
Skin Corrosion/Irritation:	No data available on PCD/Cemented Carbide
Serious Eye Damage/Eye Irritation:	No data available on PCD/Cemented Carbide
Respiratory or Skin Sensitization:	No data available on PCD/Cemented Carbide
Germ Cell Mutagenicity:	No data available on PCD/Cemented Carbide
Carcinogenicity:	Group 2A on IARC, as cobalt powder coexisting with tungsten carbide powder. Suspected to be carcinogenic in humans (Ref.1)
Reproductive Toxicity:	No data available on PCD/Cemented Carbide
Specific Target Organ Toxicity/Systemic Toxicity (Single Exposure)	No data available on PCD/Cemented Carbide
Specific Target Organ Toxicity/Systemic Toxicity (Repeated Exposure)	No data available on PCD/Cemented Carbide
Aspiration Hazard:	No data available on PCD/Cemented Carbide

12. Ecological Information

The aquatic environment acute hazard

- Not reported on PCD/Cemented Carbide

The aquatic environment chronic hazard

- Not reported on PCD/Cemented Carbide

Mobility

- Not reported on PCD/Cemented Carbide

13. Disposal Considerations

Safe and environmentally desirable disposal or recycle method

- The main ingredients such as tungsten carbide, cobalt are rare metal. It is desirable to collect and recycle them.
- For disposal, conform to the applicable laws regarding industrial wastes such as 'Waste Disposal and Public Cleansing Law' and relevant local by laws.

14. Transport Information

International Regulations

UN Number: Not applicable

UN Hazard Class: Not applicable

Marine Pollutant: Not applicable

*When transporting a powder of metallic ingredients (cobalt) for composing the PCD/Cemented Carbide, there is a possibility that it is necessary to take appropriate action in accordance with the relevant provisions established by IMO (International Maritime Organization), ICAO (International Civil Aviation Organization), IATA (International Air Transport Association).

Domestic Regulations

Land Regulatory Information: In accordance with the Fire Service Act/ the Road Act

Marine Transportation Information: In accordance with the Ship Safety Act/ the Act on Port Regulations

Marine Pollutant: Not applicable

Aviation transportation information: In accordance with the Civil Aeronautics Act

*When transporting a powder of metallic ingredients (cobalt) for composing the PCD/Cemented Carbide, there is a possibility that it is necessary to take appropriate action in accordance with the relevant provisions of Ship Safety Law and the Aviation Law.

Special Safety Measures for Transportation and Transportation Method

When transporting the dust which occurs from PCD/Cemented Carbide raw materials and producing process, make sure that there is no damage or corrosion or leakage of the container, to ensure implementation of the prevention of collapse of cargo.

15. Regulatory Information

Name and Information of Applicable Regulatory

- Law for Pollutant Release and Transfer Register (PRTR)

Cobalt: "Class 1 designated chemical substances", Cabinet Order No.132

Chromium: "Class 1 designated chemical substances", Cabinet Order No.87

- Industrial Safety and Health Law, Ordinance on Prevention of Hazards due to Specified Chemical Substances

Cobalt: The substances are defined in the Article 57-2 of the Act, and the cobalt is listed by No.172 in Appended Table9 in the Article 18-2 of the Enforcement Order as “Dangerous or Harmful Substances to be notified their names, etc.”

Article 2, Paragraph 1, Items 2 and 5 of Ordinance on Prevention of Hazards due to Specified Chemical Substance, Specified chemical substance class 2, Management class 2.

When the content of cobalt and cobalt oxide is less than 1%, the Ordinance on Prevention of Hazards due to Specified Chemical Substance is not covered.

Chromium: The substances are defined in the Article 57-2 of the Act, and the chromium is listed by No.142in Appended Table9 in the Article 18-2 of the Enforcement Order as “Dangerous or Harmful Substances to be notified their names, etc.”

16. Other Information

Other Hazardous Information

The following attention should be paid for dust which occur from PCD/Cemented Carbide producing process.

- If a large amount of dust containing cobalt is inhaled, blood, heart, thyroid gland, and spleen disorders may result. (Ref.2)
- It is reported that repeated or prolonged contact with cobalt, nickel, or chromium may affect skin, respiratory organs, heart, etc. (Ref.3 - 6)
- For carcinogenicity of metallic ingredients of CBN/Cemented Carbide has the following knowledge.

Cobalt metal	ACGIH	A3: Confirmed animal carcinogen with unknown relevance to humans.
	IARC	2B: Possibly carcinogenic to humans.
Chromium metal	Japan Society for Occupational Health	2B: The substance has been determined to be possibly carcinogenic to humans (with relatively insufficient evidence).
	IARC	3: Not classifiable as to its carcinogenicity to humans.

*ACGIH : American Conference of Governmental Industrial Hygienists Inc.

*IARC : International Agency for Research on Cancer

Disclaimer

The contents of this SDS are based on material and information available as of today and may be revised due to knowledge newly obtained. The values of concentration, physical/chemical properties are not guaranteed. In addition, the precautions described herein apply only to normal uses, and thus safety cannot be guaranteed.

Reference URL

- Ministry of Economy, Trade and Industry : <http://www.meti.go.jp/>
- Ministry of the Environment : <http://www.env.go.jp/>
- Ministry of Health, Labour and Welfare : <http://www.mhlw.go.jp/>
- Japan Industrial Safety and Health Assoc. : <http://www.jaish.gr.jp/>
- International Agency for Research on Cancer : <http://monographs.iarc.fr/>
- International Chemical Safety Card : <http://www.nihs.go.jp/ICSC/>
- National Institute of Technology and Evaluation : <http://www.safe.nite.go.jp/ghs/list.html>

Reference Documents

- (1) IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, vol.86 (2006).
- (2) Food & Drug Research Laboratories, study No.8005B (4.11.84).
- (3) T. Shirakawa et al., Chest. 95, 29 (1989).
- (4) International Chemical Safety Cards (cobalt, chromium, nickel).
- (5) The Guide to Chemical Hazards (edited by Japan Industrial Safety & Health Association)
- (6) A. O. Bech et al., Brit. J. Ind., 19, 239 (1962)

Revision History

Rev.8	3 rd April, 2023	Change of company name and update of latest information
-------	-----------------------------	---