
## Insert bar Hexalobular socket (6-LOBE hole) SSP-T






Item Number	Socket size	Socket number	L6 mm	L7 mm	Recommended Pilot bore Dia. mm	APMX mm	CW mm	DCON mm	H mm	HF mm	HF2 mm	К5 °	LF mm	LH nn	Carbide PVD coating TM4
SSP050N25T06	T6	6	1.75	1.27	1.15	2.5	1.2	5	4.75	1.09	2.4	6	70	35	•
SSP050N31T07	Τ7	-	-	-	1.38	3.1	1.4	5	4.75	1.29	2.4	6	70	35	•
SSP050N36T08	Т8	8	2.4	1.75	1.62	3.6	1.6	5	4.75	1.5	2.4	6	70	35	•
SSP050N41T10	T10	10	2.8	2.05	1.92	4.1	1.8	5	4.75	1.7	2.4	6	70	35	•
SSP050N43T15	T15	15	3.35	2.4	2.3	4.3	2.2	5	4.75	2.1	2.4	6	70	35	•
SSP050N46T20	T20	20	3.95	2.85	2.71	4.6	2.6	5	4.75	2.5	2.4	6	70	35	•
SSP050N50T25	T25	25	4.5	3.25	3.13	5	3	5	4.75	2.9	2.4	6	70	35	•
SSP050N55T27	T27	-	-	-	3.52	5.5	3.4	5	4.75	3.3	2.4	6	70	35	•
SSP050N55T30	T30	30	5.6	4.05	3.91	5.5	3.8	5	4.75	3.7	2.4	6	70	35	•

## Hexagon socket






Item Number	Base AF L4 mm	AF range L5 mm	APMX mm	CW mm	DCON mm	epsr °	H mm	HF mm	HF2 mm	К5 °	LF mm	Carbide PVD coating TM4
SSP020N06515H	1	1-1.1	1.5	0.65	2	120	1.8	0.7	0.35	15	50	•
SSP020N07018H	1.1	1.1-1.2	1.8	0.7	2	120	1.8	0.8	0.4	15	50	•
SSP020N07518H	1.2	1.2-1.3	1.8	0.75	2	120	1.8	0.9	0.45	15	50	•
SSP020N08020H	1.3	1.3-1.4	2	0.8	2	120	1.8	1	0.5	15	50	•
SSP020N1130H	1.5	1.4-1.9	3	1.1	2	120	1.8	0.9	0.45	6	50	•
SSP020N1430H	2	1.8-2.5	3	1.4	2	120	1.8	1.2	0.6	6	50	•
SSP030N1940H	3	2.3-3.5	4	1.9	3	120	2.8	1.5	0.75	6	50	•
SSP040N2450H	4	3.3-4.5	5	2.4	4	120	3.8	2.5	1.25	6	60	•
SSP050N3260H	5	4.3-6.1	6	3.2	5	120	4.8	3.3	1.65	6	70	•
SSP060N42120H	6	5.3-8.1	12	4.2	6	120	5.6	4	2	6	80	•
SSP080N62160H	8	7.3-12.1	16	6.2	8	120	7.6	4.9	2.45	6	80	•

## Square Socket





Item Number	Base AF L4 mm	AF range L5 mm	APMX mm	CW mm	DCON mm	epsr °	H mm	HF mm	HF2 mm	К5 °	LF mm	Carbide PVD coating TM4
SSP020N1740S	2	2-2.3	4	1.7	2	90	1.8	1.6	0.7	6	50	•
SSP025N1940S	2.5	2.3-2.6	4	1.95	2.5	90	2.3	1.8	0.65	6	50	•
SSP030N2260S	3	2.6-3	6	2.2	3	90	2.8	2.05	0.65	6	50	•
SSP035N2760S	3.5	2.9-3.7	6	2.7	3.5	90	3.3	2.25	0.6	6	60	•
SSP040N3380S	4	3.7-4.5	8	3.35	4	90	3.8	3.05	1.15	6	60	•
SSP050N39100S	5	4.5-5.3	10	3.9	5	90	4.8	3.95	1.55	6	70	•
SSP060N47120S	6	5.3-6.5	12	4.75	8	90	5.6	4.5	1.7	6	80	•
SSP080N58160S	8	6.5-8	16	5.8	8	90	7.6	5.5	1.7	6	80	•

L4/L5