






〈80° 菱形 ポジ〉

●第一推奨 ○第二推奨

						銅											
						ステンレス鋼											
						鋳鉄											
						非鉄金属											
						耐熱合金											
						高硬度材											
						その他（非金属）											
形状	品番	IC	S	AN	RE	超硬											
		mm	mm	°	mm	PVD 650	PVD ST4	PVD DM4	PVD DT4	PVD QM3	PVD TM4	PVD VM1	PVD ZM3	CVD CP1	CVD CP7	コーティング	
	CCGT 09T301M R TMV	9.525	3.97	7	0.08	●	●	●			●						
	CCGT 09T302M R TMV	9.525	3.97	7	0.18	●	●	●			●						
	CCGT 09T304M R TMV	9.525	3.97	7	0.38	●	●	●			●						
	CCGT 09T300 YL	9.525	3.97	7	0.03				●		●						
	CCGT 09T301M YL	9.525	3.97	7	0.08	●	●	●	●	●	●						
	CCGT 09T302M YL	9.525	3.97	7	0.18	●	●	●	●	●	●						
	CCGT 09T304M YL	9.525	3.97	7	0.38	●	●	●	●	●	●						
	CCGT 09T308M YL	9.525	3.97	7	0.78		●	●	●	●	●						
	CCGT 060201M CL	6.35	2.38	7	0.08		●	●	●	●	●						
	CCGT 060202M CL	6.35	2.38	7	0.18		●	●	●	●	●						
	CCGT 09T300 CL	9.525	3.97	7	0.03				●		●						
	CCGT 09T301M CL	9.525	3.97	7	0.08	●	●	●	●	●	●						
	CCGT 09T302M CL	9.525	3.97	7	0.18	●	●	●	●	●	●						
	CCGT 09T304M CL	9.525	3.97	7	0.38	●	●	●	●	●	●						
	CCGT 060200 FN AM3	6.35	2.38	7	0.03				●		●	●					
	CCGT 060201M FN AM3	6.35	2.38	7	0.08		●		●	●	●						
	CCGT 060202 FN AM3	6.35	2.38	7	0.2				●	●	●	●	●				
	CCGT 060202M FN AM3	6.35	2.38	7	0.18		●		●	●	●						
	CCGT 060204 FN AM3	6.35	2.38	7	0.4								●				
	CCGT 060204M FN AM3	6.35	2.38	7	0.38		●		●	●	●						
	CCGT 09T300 FN AM3	9.525	3.97	7	0.03				●		●	●					
	CCGT 09T301M FN AM3	9.525	3.97	7	0.08	●	●		●	●	●	●	●				
	CCGT 09T302 FN AM3	9.525	3.97	7	0.2					●	●	●	●				
	CCGT 09T302M FN AM3	9.525	3.97	7	0.18	●	●		●	●	●	●	●				
	CCGT 09T304 FN AM3	9.525	3.97	7	0.4					●	●	●	●				
	CCGT 09T304M FN AM3	9.525	3.97	7	0.38	●	●		●	●	●	●	●				
	CCMT 060202 FN AM3	6.35	2.38	7	0.2			●									
	CCMT 060204 FN AM3	6.35	2.38	7	0.4			●									
	CCMT 09T302 FN AM3	9.525	3.97	7	0.2			●									
	CCMT 09T304 FN AM3	9.525	3.97	7	0.4			●									
	CCMT 09T308 FN AM3	9.525	3.97	7	0.8			●									
	CCGT 060200 AZ7	6.35	2.38	7	0.03					●							
	CCGT 060201M AZ7	6.35	2.38	7	0.08					●							
	CCGT 060202M AZ7	6.35	2.38	7	0.18					●							
	CCGT 09T300 AZ7	9.525	3.97	7	0.03				●	●	●		●				
	CCGT 09T301M AZ7	9.525	3.97	7	0.08				●	●	●		●				
	CCGT 09T302M AZ7	9.525	3.97	7	0.18				●	●	●		●				
	CCGT 09T304M AZ7	9.525	3.97	7	0.38				●	●	●		●				
	CCMT 060202 E002 AZ8	6.35	2.38	7	0.2											●	
	CCMT 060204 E004 AZ8	6.35	2.38	7	0.4											●	
	CCMT 060208 E004 AZ8	6.35	2.38	7	0.8											●	
	CCMT 09T302 E002 AZ8	9.525	3.97	7	0.2											●	
	CCMT 09T304 E004 AZ8	9.525	3.97	7	0.4											●	
	CCMT 09T308 E004 AZ8	9.525	3.97	7	0.8											●	

新製品 N

製品紹介 O

材種・選択ガイド P

前抜き加工 Q

後抜き加工 R

突切り加工 S

溝入れ加工 T

ねじ切り加工 U




内径加工 V

シェーパー W

エンドミル X


技術資料 Y




索引 Z

						銅		○	○	●	●	●	●	●	●	●	●	●	●		
						ステンレス鋼		○	●	○	○	○	●	○	●	●	●	●	●	●	●
						鋳鉄													●		
						非鉄金属							○		○						●
						耐熱合金		●		●	○	○									
						高硬度材				○	○	○									
						その他（非金属）															●
形状	品番	IC	S	AN	RE	超硬															
		mm	mm	°	mm	PVD 650	PVD ST4	PVD DM4	PVD DT4	PVD QM3	PVD TM4	PVD VM1	PVD ZM3	CVD CP1	CVD CP7	コー ティング KM1					
	CCGT 060200 R S	6.35	2.38	7	0.03				●			●	●								
	CCGT 060200 L S	6.35	2.38	7	0.03							●	●								
	CCGT 060201M R S	6.35	2.38	7	0.08				●	●			●	●							
	CCGT 060201 R S	6.35	2.38	7	0.1							●	●								
	CCGT 060201 L S	6.35	2.38	7	0.1							●	●								
	CCGT 060202M R S	6.35	2.38	7	0.18				●	●			●	●							
	CCGT 060202 R S	6.35	2.38	7	0.2							●	●								
	CCGT 060202 L S	6.35	2.38	7	0.2							●	●								
	CCGT 09T300 R S	9.525	3.97	7	0.03				●		●	●	●								
	CCGT 09T300 L S	9.525	3.97	7	0.03							●									
	CCGT 09T301M R S	9.525	3.97	7	0.08				●	●	●		●								
	CCGT 09T301 R S	9.525	3.97	7	0.1					●		●	●								
	CCGT 09T301 L S	9.525	3.97	7	0.1							●	●								
	CCGT 09T302M R S	9.525	3.97	7	0.18				●	●	●		●								
	CCGT 09T302 R S	9.525	3.97	7	0.2					●			●								
	CCGT 09T302 L S	9.525	3.97	7	0.2							●									
CCGT 09T304M R S	9.525	3.97	7	0.38				●	●	●											
CCGT 09T304 R S	9.525	3.97	7	0.4					●												
	CCGT 060200 R U	6.35	2.38	7	0.03				●				●								
	CCGT 060201 R U	6.35	2.38	7	0.1				●				●								
	CCGT 060201 L U	6.35	2.38	7	0.1								●								
	CCGT 060202 R U	6.35	2.38	7	0.2				●				●								
	CCGT 060202 L U	6.35	2.38	7	0.2								●								
	CCGT 09T300 R U1	9.525	3.97	7	0.03				●		●		●								
	CCGT 09T300 L U1	9.525	3.97	7	0.03								●								
	CCGT 09T301 R U1	9.525	3.97	7	0.1				●		●		●								
	CCGT 09T301 L U1	9.525	3.97	7	0.1								●								
	CCGT 09T302 R U1	9.525	3.97	7	0.2				●		●		●								
	CCGT 09T302 L U1	9.525	3.97	7	0.2								●								
	CCGT 09T304 R U1	9.525	3.97	7	0.4				●		●		●								
CCGT 09T304 L U1	9.525	3.97	7	0.4								●									
	CCET 0602005 R KHG	6.35	2.38	7	0.05							●									
	CCET 0602005 L KHG	6.35	2.38	7	0.05							●									
	CCET 0602008 R KHG	6.35	2.38	7	0.08							●									
	CCET 0602008 L KHG	6.35	2.38	7	0.08							●									
	CCET 0602018 R KHG	6.35	2.38	7	0.18							●									
	CCET 0602018 L KHG	6.35	2.38	7	0.18							●									
	CCET 060202 R KHG	6.35	2.38	7	0.2							●									
	CCET 060202 L KHG	6.35	2.38	7	0.2							●									
	CCET 09T3005 R KHG	9.525	3.97	7	0.05						●	●									
	CCET 09T3005 L KHG	9.525	3.97	7	0.05							●									
	CCET 09T3008 R KHG	9.525	3.97	7	0.08						●	●									
	CCET 09T3008 L KHG	9.525	3.97	7	0.08							●									
	CCET 09T3018 R KHG	9.525	3.97	7	0.18						●	●									
	CCET 09T3018 L KHG	9.525	3.97	7	0.18							●									
CCET 09T302 R KHG	9.525	3.97	7	0.2						●	●										
CCET 09T302 L KHG	9.525	3.97	7	0.2							●										
	CCGT 060201 FR F1	6.35	2.38	7	0.1		●			●	●										
	CCGT 060202 FR F1	6.35	2.38	7	0.2		●			●	●										
	CCGT 060204 FR F1	6.35	2.38	7	0.4		●			●	●										
	CCGT 09T302 FR F1	9.525	2.38	7	0.2		●			●	●										
	CCGT 09T304 FR F1	9.525	2.38	7	0.4		●			●	●										
	CCGW 060200 FN	6.35	2.38	7	0.03								●								
	CCGW 060200 H 	6.35	2.38	7	0.03											●					
	CCGW 060201 FN	6.35	2.38	7	0.1								●								
	CCGW 060201 H 	6.35	2.38	7	0.1											●					
	CCGW 060202 H 	6.35	2.38	7	0.2											●					
	CCGW 09T30 V 	9.525	3.97	7	0							●									
	CCGW 09T300 FN	9.525	3.97	7	0.03								●								
CCGW 09T300 H 	9.525	3.97	7	0.03											●						

〈55° 菱形 ポジ〉

●第一推奨 ○第二推奨

							銅											○	○	●	●	●	●	●	●	●	●	●	●	●	●		
							ステンレス鋼											○	●	○	○	○	●	○	●					●			
							鋳鉄																							●			
							非鉄金属																○		○							●	
							耐熱合金													●	○	○											
							高硬度材													○	○	○											
							その他（非金属）																							●			

形状	品番	IC	S	AN	RE	BS	超硬															ト ン コ ー ン
							PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	CVD	CVD				
		mm	mm	°	mm	mm	650	ST4	DM4	DT4	QM3	TM4	VM1	ZM3	CP1	CP7	KM1					
	DCGT 11T301M R TMV	9.525	3.97	7	0.08	-	●	●	●			●										
	DCGT 11T302M R TMV	9.525	3.97	7	0.18	-	●	●	●			●										
	DCGT 11T304M R TMV	9.525	3.97	7	0.38	-	●	●	●			●										
	DCGT 070201M YL	6.35	2.38	7	0.08	-			●		●											
	DCGT 070202M YL	6.35	2.38	7	0.18	-			●		●											
	DCGT 070204M YL	6.35	2.38	7	0.38	-			■		■											
	DCGT 11T300 YL	9.525	3.97	7	0.03	-					●		●									
	DCGT 11T301M YL	9.525	3.97	7	0.08	-	●	●	●	●	●	●										
	DCGT 11T302M YL	9.525	3.97	7	0.18	-	●	●	●	●	●	●										
	DCGT 11T304M YL	9.525	3.97	7	0.38	-	●	●	●	●	●	●										
	DCGT 11T308M YL	9.525	3.97	7	0.78	-		●	●	●	●	●										
	DCGT 070201M CL	6.35	2.38	7	0.08	-		●	●	●	●	●										
	DCGT 070202M CL	6.35	2.38	7	0.18	-		●	●	●	●	●										
	DCGT 070204M CL	6.35	2.38	7	0.38	-		●	●	●	●	●										
	DCGT 11T301M CL	9.525	3.97	7	0.08	-	●	●	●	●	●	●										
	DCGT 11T302M CL	9.525	3.97	7	0.18	-	●	●	●	●	●	●										
	DCGT 11T304M CL	9.525	3.97	7	0.38	-	●	●	●	●	●	●										
	DCGT 070200 FN AM3	6.35	2.38	7	0.03	-				●		●	●	●								
	DCGT 070201 FN AM3	6.35	2.38	7	0.1	-						●	●	●								
	DCGT 070202 FN AM3	6.35	2.38	7	0.2	-						●	●	●								
	DCGT 070204 FN AM3	6.35	2.38	7	0.4	-						●	●	●								
	DCGT 070201M FN AM3	6.35	2.38	7	0.08	-		●		●	●	●										
	DCGT 070202M FN AM3	6.35	2.38	7	0.18	-		●		●	●	●										
	DCGT 070204M FN AM3	6.35	2.38	7	0.38	-		●		●	●	●										
	DCGT 11T300 FN AM3	9.525	3.97	7	0.03	-				●		●	●	●								
	DCGT 11T301M FN AM3	9.525	3.97	7	0.08	-	●	●		●	●	●	●	●	●							
	DCGT 11T302 FN AM3	9.525	3.97	7	0.2	-					●	●	●	●	●							
	DCGT 11T302M FN AM3	9.525	3.97	7	0.18	-	●	●		●	●	●	●	●	●							
	DCGT 11T304 FN AM3	9.525	3.97	7	0.4	-				●	●	●	●	●	●							
	DCGT 11T304M FN AM3	9.525	3.97	7	0.38	-	●	●		●	●	●	●	●	●							
	DCMT 070202 FN AM3	6.35	2.38	7	0.2	-			●													
	DCMT 070204 FN AM3	6.35	2.38	7	0.4	-			●													
	DCMT 11T302 FN AM3	9.525	3.97	7	0.2	-			●													
	DCMT 11T304 FN AM3	9.525	3.97	7	0.4	-			●													
	DCMT 11T308 FN AM3	9.525	3.97	7	0.8	-			●													
	DCGT 070200 AMX	6.35	2.38	7	0.03	-			●			●										
	DCGT 070201M AMX	6.35	2.38	7	0.08	-		●	●	●		●										
	DCGT 070202M AMX	6.35	2.38	7	0.18	-		●	●	●		●										
	DCGT 070204M AMX	6.35	2.38	7	0.38	-			●	●		●										
	DCGT 11T300 AMX	9.525	3.97	7	0.03	-			●			●										
	DCGT 11T301M AMX	9.525	3.97	7	0.08	-	●	●	●	●		●										
	DCGT 11T302M AMX	9.525	3.97	7	0.18	-	●	●	●	●		●										
	DCGT 11T304M AMX	9.525	3.97	7	0.38	-	●	●	●	●		●										
	DCGT 070200 AZ7	6.35	2.38	7	0.03	-					●											
	DCGT 070201M AZ7	6.35	2.38	7	0.08	-					●											
	DCGT 070202M AZ7	6.35	2.38	7	0.18	-					●											
	DCGT 11T300 AZ7	9.525	3.97	7	0.03	-				●	●	●		●								
	DCGT 11T301M AZ7	9.525	3.97	7	0.08	-				●	●	●		●								
	DCGT 11T302M AZ7	9.525	3.97	7	0.18	-				●	●	●		●								
	DCGT 11T304M AZ7	9.525	3.97	7	0.38	-				●	●	●		●								
	DCGT 11T308 AZ7	9.525	3.97	7	0.8	-				●	●			●								
	DCMT 11T304 E004 AZ8	9.525	3.97	7	0.4	-										●						
	DCMT 11T308 E004 AZ8	9.525	3.97	7	0.8	-										●						

新製品 N

製品紹介 O

材種・選択ガイド P

前抜き加工 Q

後抜き加工 R

突切り加工 S

溝入れ加工 T

ねじ切り加工 U





内径加工 V

シェーパー W


エンドミル X

技術資料 Y

索引 Z

							銅																
							ステンレス鋼																
							鋳鉄																
							非鉄金属																
							耐熱合金																
							高硬度材																
その他（非金属）																							
形状	品番	IC	S	AN	RE	BS	超硬																
		mm	mm	°	mm	mm	PVD 650	PVD ST4	PVD DM4	PVD DT4	PVD QM3	PVD TM4	PVD VM1	PVD ZM3	CVD CP1	CVD CP7	ト ン コ ー ン						
	DCGT 070200 R S	6.35	2.38	7	0.03	-					●				●	●							
	DCGT 070200 L S	6.35	2.38	7	0.03	-									●	●							
	DCGT 070201M R S	6.35	2.38	7	0.08	-					●	●											
	DCGT 070201 R S	6.35	2.38	7	0.1	-									●	●							
	DCGT 070201 L S	6.35	2.38	7	0.1	-									●	●							
	DCGT 070202M R S	6.35	2.38	7	0.18	-					●	●											
	DCGT 070202 R S	6.35	2.38	7	0.2	-									●	●							
	DCGT 070202 L S	6.35	2.38	7	0.2	-									●	●							
	DCGT 070204 R S	6.35	2.38	7	0.4	-									●	●							
	DCGT 11T300 R S	9.525	3.97	7	0.03	-					●		●		●	●							
	DCGT 11T300 L S	9.525	3.97	7	0.03	-									●								
	DCGT 11T301M R S	9.525	3.97	7	0.08	-					●	●	●										
	DCGT 11T301 R S	9.525	3.97	7	0.1	-						●			●	●							
	DCGT 11T301 L S	9.525	3.97	7	0.1	-									●								
	DCGT 11T302M R S	9.525	3.97	7	0.18	-					●	●	●										
	DCGT 11T302 R S	9.525	3.97	7	0.2	-						●			●	●							
DCGT 11T302 L S	9.525	3.97	7	0.2	-									●									
DCGT 11T304M R S	9.525	3.97	7	0.38	-					●	●	●											
DCGT 11T304 R S	9.525	3.97	7	0.4	-						●												
	DCGT 070200 R U	6.35	2.38	7	0.03	-								●	●								
	DCGT 070201 R U	6.35	2.38	7	0.1	-								●	●								
	DCGT 070202 R U	6.35	2.38	7	0.2	-								●	●								
	DCGT 070202 L U	6.35	2.38	7	0.2	-									●	●							
	DCGT 11T300 R U1	9.525	3.97	7	0.03	-					●		●	●	●								
	DCGT 11T300 L U1	9.525	3.97	7	0.03	-									●								
	DCGT 11T301 R U1	9.525	3.97	7	0.1	-					●		●	●	●								
	DCGT 11T301 L U1	9.525	3.97	7	0.1	-							●	●	●								
	DCGT 11T302 R U1	9.525	3.97	7	0.2	-					●		●	●	●								
	DCGT 11T302 L U1	9.525	3.97	7	0.2	-								●	●								
	DCGT 11T304 R U1	9.525	3.97	7	0.4	-					●		●	●	●								
	DCGT 11T304 L U1	9.525	3.97	7	0.4	-									●								
	DCET 0702005 R KHG	6.35	2.38	7	0.05	-								●									
	DCET 0702005 L KHG	6.35	2.38	7	0.05	-								●									
	DCET 0702008 R KHG	6.35	2.38	7	0.08	-								●									
	DCET 0702008 L KHG	6.35	2.38	7	0.08	-								●									
	DCET 0702018 R KHG	6.35	2.38	7	0.18	-								●									
	DCET 0702018 L KHG	6.35	2.38	7	0.18	-								●									
	DCET 070202 R KHG	6.35	2.38	7	0.2	-								●									
	DCET 070202 L KHG	6.35	2.38	7	0.2	-								●									
	DCET 11T3005 R KHG	9.525	3.97	7	0.05	-							●	●									
	DCET 11T3005 L KHG	9.525	3.97	7	0.05	-								●									
	DCET 11T3008 R KHG	9.525	3.97	7	0.08	-							●	●									
	DCET 11T3008 L KHG	9.525	3.97	7	0.08	-								●									
	DCET 11T3018 R KHG	9.525	3.97	7	0.18	-							●	●									
	DCET 11T3018 L KHG	9.525	3.97	7	0.18	-								●									
	DCET 11T302 R KHG	9.525	3.97	7	0.2	-							●	●									
DCET 11T302 L KHG	9.525	3.97	7	0.2	-								●										
	DCET 0702008 R UHG	6.35	2.38	7	0.08	-								●									
	DCET 11T3008 R UHG	9.525	3.97	7	0.08	-								●									
	DCET 11T301M RAT 	9.525	3.97	7	0.08	-							●										
	DCET 11T302M RAT 	9.525	3.97	7	0.18	-							●										
	DCGT 11T301M R TMV -WP	9.525	3.97	7	0.08	(0.3)	●	●	●				●										
	DCGT 11T302M R TMV -WP	9.525	3.97	7	0.18	(0.3)	●	●	●				●										
	DCGT 11T3005 AM3 -WP	9.525	3.97	7	0.05	(0.3)	●	●	●	●	●												
	DCGT 11T3015 AM3 -WP	9.525	3.97	7	0.15	(0.3)	●	●	●	●	●												

〈 35° 菱形 ポジ 〉 ●第一推奨 ○第二推奨

						銅													
						ステンレス鋼													
						鋳鉄													
						非鉄金属													
						耐熱合金													
						高硬度材													
						その他（非金属）													
形状	品番	IC	S	AN	RE	超硬													
						PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	CVD	CVD	コーン／ノコン	
		mm	mm	°	mm	650	ST4	DM4	DT4	QM3	TM4	VM1	ZM3	CP1	CP7	KM1			
	VBGT 160402 FN YL	9.525	4.76	5	0.2		●	●			●								
	VBGT 160404 FN YL	9.525	4.76	5	0.4		●	●			●								
	VBGT 160408 FN YL	9.525	4.76	5	0.8		●	●			●								

※ホルダ：受注生産で対応致します。詳しくは弊社営業にお問い合わせください。


推奨切削条件 → Q4

VC..シリーズ／インサート 超硬



VC..

●第一推奨 ○第二推奨

〈35° 菱形 ポジ〉



銅	○	○	●	●	●	●	●	●		●	
ステンレス鋼	○	●	○	○	○	●	○	●		●	
鋳鉄									●		
非鉄金属						○		○			●
耐熱合金	●		●	○	○						
高硬度材			○	○	○						
その他（非金属）											●

形状	品番	IC	S	AN	RE	BS	超硬											ノ ン コ ー ト
							PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	
		mm	mm	°	mm	mm	650	ST4	DM4	DT4	QM3	TM4	VM1	ZM3	CP1	CP7	KM1	
	VCMT 110302M R TMV	6.35	3.18	7	0.18	-	●	●										
	VCMT 110304M R TMV	6.35	3.18	7	0.38	-	●	●										
	VCGT 110301M YL	6.35	3.18	7	0.08	-	●	●	●	●	●	●						
	VCGT 110302M YL	6.35	3.18	7	0.18	-	●	●	●	●	●	●						
	VCGT 110304M YL	6.35	3.18	7	0.38	-	●	●	●	●	●	●						
	VCGT 110202M CL	6.35	2.38	7	0.18	-			●	●	●	●						
	VCGT 110301M CL	6.35	3.18	7	0.08	-	●	●	●	●	●	●						
	VCGT 110302M CL	6.35	3.18	7	0.18	-	●	●	●	●	●	●						
	VCGT 110300 FN AM3	6.35	3.18	7	0.03	-				●		●	●					
	VCGT 110301M FN AM3	6.35	3.18	7	0.08	-	●	●		●	●	●	●					
	VCGT 110301 FN AM3	6.35	3.18	7	0.1	-				●	●	●		●				
	VCGT 110302M FN AM3	6.35	3.18	7	0.18	-	●	●		●	●	●	●					
	VCGT 110302 FN AM3	6.35	3.18	7	0.2	-						●	●					
	VCGT 110304M FN AM3	6.35	3.18	7	0.38	-	●	●		●	●	●	●					
	VCMT 110302 FN AM3	6.35	3.18	7	0.2	-			●									
	VCMT 110304 FN AM3	6.35	3.18	7	0.4	-			●									
	VCGT 110300 AZ7	6.35	3.18	7	0.03	-					●				●			
	VCGT 110301M AZ7	6.35	3.18	7	0.08	-					●				●			
	VCGT 110302M AZ7	6.35	3.18	7	0.18	-					●				●			
	VCGT 110304M AZ7	6.35	3.18	7	0.38	-					●				●			
	VCGT 130300 FR 2M	7.94	3.18	7	-	-			●									
	VCGT 130300 FL 2M	7.94	3.18	7	-	-			●									
	VCGT 130301 FR 2M	7.94	3.18	7	-	-			●									
	VCGT 130301 FL 2M	7.94	3.18	7	-	-			●									
	VCGT 110300 R U	6.35	3.18	7	0.03	-							●	●				
	VCGT 110301M R U	6.35	3.18	7	0.08	-				●								
	VCGT 110301 R U	6.35	3.18	7	0.1	-							●	●				
	VCGT 110302M R U	6.35	3.18	7	0.18	-				●								
	VCGT 110302 R U	6.35	3.18	7	0.2	-							●	●				
	VCET 1103008 R UHG	6.35	3.18	7	0.08	-							●					
	VCGT 1103005 R U -WP	6.35	3.18	7	0.05	(0.2)							●	●				
	VCGT 110301 R U -WP	6.35	3.18	7	0.1	(0.2)							●	●				
	VCGT 1103005 R SX -WP	6.35	3.18	7	0.05	(0.2)							●	●				
	VCGT 110301 R SX -WP	6.35	3.18	7	0.1	(0.2)							●	●				
	VCGW 110300 H	6.35	3.18	7	0.03	-											●	
	VCGW 110301 H	6.35	3.18	7	0.1	-											●	
	VCGW 110302 H	6.35	3.18	7	0.2	-											●	

参照ページ：ホルダ → Q40～Q47 推奨切削条件 → Q4

VCMT-WPインサートの特長




- 形状はVCGT型と同じです。
- ホルダにセットした状態で0.2mmのストレート（さらい刃）が付く設計になっており、ワーク面粗さの向上及び高送り可能なタイプです。
- 切れ刃角が93°のホルダ（SVJC-N）に装着可能です。

VP..シリーズ／インサート 超硬

VP..

〈35° 菱形 ポジ〉

●第一推奨 ○第二推奨

						銅	○	○	●	●	●	●	●	●	●	●	●	●	●	●				
						ステンレス鋼	○	●	○	○	○	●	○	●		●						●		
						鋳鉄																●		
						非鉄金属									○			○						●
						耐熱合金	●			●	○	○												
						高硬度材				○	○	○												
						その他（非金属）																		●
形状	品番	IC	S	AN	RE	超硬												コーンノ KM1						
						PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	CVD	CVD							
		mm	mm	°	mm	650	ST4	DM4	DT4	QM3	TM4	VM1	ZM3	CP1	CP7									
	VPET 0802005 R KHG	4.76	2.38	11	0.05						●	●												
	VPET 0802005 L KHG	4.76	2.38	11	0.05						●	●												
	VPET 0802008 R KHG	4.76	2.38	11	0.08				●		●	●												
	VPET 0802008 L KHG	4.76	2.38	11	0.08						●	●												
	VPET 0802018 R KHG	4.76	2.38	11	0.18						●	●												
	VPET 0802018 L KHG	4.76	2.38	11	0.18						●	●												
	VPET 080202 R KHG	4.76	2.38	11	0.2						●	●												
	VPET 080202 L KHG	4.76	2.38	11	0.2						●	●												
	VPET 1103005 R KHG	6.35	3.18	11	0.05						●	●												
	VPET 1103005 L KHG	6.35	3.18	11	0.05						●	●												
	VPET 1103008 R KHG	6.35	3.18	11	0.08						●	●												
	VPET 1103008 L KHG	6.35	3.18	11	0.08						●	●												
	VPET 1103018 R KHG	6.35	3.18	11	0.18						●	●												
	VPET 1103018 L KHG	6.35	3.18	11	0.18						●	●												
	VPET 110302 R KHG	6.35	3.18	11	0.2						●	●												
	VPET 110302 L KHG	6.35	3.18	11	0.2						●	●												
	VPET 0802008 L UHG	4.76	2.38	11	0.08				●															
	VPET 0802008 R UHG	4.76	2.38	11	0.08				●															
	VPGT 110300 FN AM3	6.35	3.18	11	0.03				●		●													
	VPGT 110301M FN AM3	6.35	3.18	11	0.08		●		●	●	●													
	VPGT 110302M FN AM3	6.35	3.18	11	0.18		●		●	●	●													

参照ページ：ホルダ → Q50～Q52 推奨切削条件 → Q4

新製品
N

製品紹介
O

材種・選択ガイド
P

前挽き加工
Q

後挽き加工
R

突切り加工
S

溝入れ加工
T

ねじ切り加工
U

内径加工
V

シェーパー
W



エンドミル
X

技術資料
Y

索引
Z

〈60° 正三角形 ネガ〉

●第一推奨 ○第二推奨

					銅	○	○	●	●	●	●	●	●		●	
					ステンレス鋼	○	●	○	○	○	●	○	●		●	
					鋳鉄									●		
					非鉄金属						○		○			●
					耐熱合金	●		●	○	○						
					高硬度材			○	○	○						
					その他（非金属）											●
形状	品番	IC	S	RE	超硬											
					PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	PVD	CVD	CVD	トーコンノ
		mm	mm	mm	6S0	ST4	DM4	DT4	QM3	TM4	VM1	ZM3	CP1	CP7	KM1	
	TNGG 160402M R TMV	9.525	4.76	0.18	●	●	●			●						
	TNGG 160404M R TMV	9.525	4.76	0.38	●	●	●			●						
	TNMG 160401M FN UL	9.525	4.76	0.08	●	●	●		●	●						
	TNMG 160402M FN UL	9.525	4.76	0.18	●	●	●		●	●						
	TNMG 160404M FN UL	9.525	4.76	0.38	●	●	●		●	●						
	TNMG 160408M FN UL	9.525	4.76	0.78		●	●		●	●						
	TNMG 160402 FN ZP	9.525	4.76	0.2			●		●	●	●	●				
	TNMG 160404 FN ZP	9.525	4.76	0.4			●		●	●	●	●				
	TNMG 160408 FN ZP	9.525	4.76	0.8			●		●		●	●				
	TNMG 160408 G	9.525	4.76	0.8									●			
	TNMG 160412 G	9.525	4.76	1.2									●			
	TNMG 160404 T00525 Z5	9.525	4.76	0.4			●		●							
	TNMG 160408 T00525 Z5	9.525	4.76	0.8			●		●							
	TNEG 160402 FL D1	9.525	4.76	0.2						●						
	TNEG 160402 FR D1	9.525	4.76	0.2						●						
	TNEG 160404 FL D1	9.525	4.76	0.4						●						
	TNEG 160404 FR D1	9.525	4.76	0.4						●						
	TNEG 160408 FL D1	9.525	4.76	0.8						●						
	TNEG 160408 FR D1	9.525	4.76	0.8						●						
	TNMG 160401 FR U2	9.525	4.76	0.1							●	●				
	TNMG 160402 FL U2	9.525	4.76	0.2			●					●				
	TNMG 160402 FR U2	9.525	4.76	0.2			●					●				
	TNMG 160404 FL U2	9.525	4.76	0.4			●					●				
	TNMG 160404 FR U2	9.525	4.76	0.4			●					●				
	TNMG 160408 FL U2	9.525	4.76	0.8								●				
	TNMG 160408 FR U2	9.525	4.76	0.8								●				
	TNMG 160402 FR C	9.525	4.76	0.2								●				
	TNMG 160401 FR DA	9.525	4.76	0.1							●	●				

